



3956 Mogadore Industrial Parkway
Mogadore, Ohio USA 44260-1201

330-628-6230
Fax: 330-628-6231
www.vertexseals.com

PURE LUBE 400/400 S.A. & 500



**CERTIFIED TO
NSF/ANSI 61**

**FOR LUBRICATING SLIP-ON OR "O" RING TYPE JOINTS
WITH RUBBER OR SYNTHETIC RUBBER GASKET SEALS**

DESCRIPTION:

PURE LUBE 400/400SA is designed for lubricating slip-on or "O" Ring type joints without harming rubber or plastic gaskets. It adheres to both wet or dry surfaces and is a subaqueous lubricant. No taste or odor is transferred to fluids in pipe system. PURE LUBE 400 is non toxic, biodegradable and does not support bacteria growth, and is approved for potable water pipe.

SPECIFICATIONS: **MEETS OR EXCEEDS ASTM C497M-03a** **TEMP. RANGE -10 F. TO 125 F.**
NSF CERTIFIED TO ANSI/NSF 61

APPLICATION: Follow product installation guide for complete lubrication and assembly instructions as supplied by the gasketed pipe manufacturers.

DIRECTIONS:

- PURE LUBE 400/400SA is ready to use. Do not dilute or alter its consistency in any way.
- If liquid appears on surface, simply mix well before using.
- Clean gasket seal and joining surfaces thoroughly.
- Make sure gasket seal is properly seated.
- Apply PURE LUBE 400/400SA moderately and evenly over required lubrication surface with a sponge, cloth, gloved hand or brush. Avoid excessive amount and dry spots.
- Do not apply directly in gasket seal seating groove.
- Assemble joint following approved coupling method.

WEIGHTS & VOLUMES

	Pail Size (US Gal)	Weight	Pails Per Skid
Actual	Quart	2 lbs.	600
Approx.			12 per Ctn.
Actual	1 Gallon	8 lbs	180
Approx.			4 per Ctn.
Actual	3.5 Gallon	30 lbs	48 Pails
Approx.			
Actual	5 Gallon	40 lbs	36 Pails
Approx.			
Actual	55 Gallon	500 lbs	4 Drums
Approx.			

CAUTION: This lubricant soap. Prolonged contact with

Avoid contact with eyes. If contacted with eyes, flush 5 minutes with clan water. If discomfort persists, obtain medical attention. Keep container closed when not in use. Keep out of reach of children.

has the characteristics of skin may cause irritation.

UPDATED 3-7-14

The information presented herein is based on the data available and is believed to be correct. However, nothing stated in this bulletin is to be taken as a warranty, expressed or implied regarding the accuracy of the information of the use of our product used singly or in conjunction with other products.